



DEFINITIONS & ACRONYMS

DRAFT



Term/Acronym	Definition
A4, A5	A standard for converting gases to carbon dioxide equivalents using the Intergovernmental Panel on Climate Change global warming protocols.
AARG	average annual rate of growth
AB 32	California Global Warming Solutions Act of 2006, which mandates a carbon price to be applied to all power generated in or sold into that state.
ACE	Area Control Error
ACE Rule	Affordable Clean Energy Rule. Adopted in 2018, EPA's replacement for the Clean Power Plant Rule.
ADMS	Advanced Distribution Management System, a computer-based, integrated platform that provides the tools to monitor and control distribution networks in real time.
AECO	Alberta Energy Company, a natural gas hub in Alberta, Canada.
AMI	advanced metering infrastructure
AMR	automated meter reading
aMW	The average number of megawatt-hours (MWh) over a specified time period; for example, 175,200 MWh generated over the course of one year equals 20 aMW (175,200 / 8,760 hours).
AOC	Administrative Order of Consent
ARMA	autoregressive moving average
ATC	available transmission capacity
AURORA	One of the models PSE uses for electric resource planning. AURORA uses the western power market to produce hourly electricity price forecasts of potential future market conditions. AURORA is also used to test electric portfolios to evaluate PSE's long-term revenue requirements.
BA	Balancing Authority, the area operator that matches generation with load.
BAA	Balancing Authority area
BACT	Best available control technology, required of new power plants and those with major modifications, pursuant to EPA regulations.
balancing reserves	Reserves sufficient to maintain system reliability within the operating hour; this includes frequency support, managing load and variable resource forecast error, and actual load and generation deviations. Balancing reserves must be able to ramp up and down as loads and resources fluctuate instantaneously each hour.
BART	Best available retrofit technology, an EPA requirement for certain power plant modifications.
Base Scenario	In an analysis, a set of assumptions that is used as a reference point against which other sets of assumptions can be compared. The analysis result may not ultimately indicate that the Base Scenario assumptions should govern decision-making.
Baseload combustion turbines	Baseload combustion turbines are designed to operate economically and efficiently over long periods of time, which is defined as more than 60 percent of the hours in a year. Generally combined-cycle combustion turbines (CCCTs).



Term/Acronym	Definition
baseload resources	Baseload resources produce energy at a constant rate over long periods at lower cost relative to other production facilities; typically used to meet some or all of a region's continuous energy need.
BAU	business-as-usual
Bcf	billion cubic feet
BEM	Business Energy Management sector, for electric energy efficiency programs.
BES	bulk electric system
BESS	battery energy storage system
BPA	Bonneville Power Administration
BSER	Best system of emissions reduction, an EPA requirement for certain power plant construction or modification.
BTU	British thermal units
CAA	Clean Air Act
CAISO	California Independent System Operator
capacity factor	The ratio of the actual generation from a power resource compared to its potential output if it was possible to operate at full nameplate capacity over the same period of time.
CAP	Corrective action plan, a series of operational steps used to prevent system overloads or loss of customer power.
CAR	Washington State Clean Air Rule
CARB	California Air Resources Board
CBI	customer benefit indicator
CCCT	Combined-cycle combustion turbine. Baseload generating plant that consists of one or more combustion turbine generators equipped with heat recovery steam generators that capture heat from the combustion turbine exhaust and use it to produce additional electricity via a steam turbine generator.
CCR	coal combustion residuals
CCS	carbon capture and sequestration
CDD	cooling degree day
CEAP	Clean Energy Action Plan
CEC	California Energy Commission
CEIP	Clean Energy Implementation Plan
CETA	Clean Energy Transformation Act
CFS	conditional firm service, a new transmission product offered by BPA.
CHP	combined heat and power
CI	confidence interval



Term/Acronym	Definition
CIA	cumulative impact analysis
CIA	community impact assessment
C&I	commercial and industrial
CNG	compressed natural gas
CO ₂	carbon dioxide
CO ₂ e	carbon dioxide equivalents
COE	U.S. Army Corps of Engineers
contingency reserves	Reserves added in addition to balancing reserves; contingency reserves are intended to bolster short-term reliability in the event of forced outages and are used for the first hour of the event only. This capacity must be available within 10 minutes, and 50 percent of it must be spinning.
CPA	conservation potential assessment
CPI	consumer price index
CPP	federal Clean Power Plan
CPP	critical peak pricing or dynamic pricing
CPUC	California Public Utilities Commission
CRAG	PSE's Conservation Resource Advisory Group
C&S	codes and standards
CT	combustion turbine
CVR	conservation voltage reduction
DA	distribution automation
DE	distribution efficiency
DER	distributed energy resources
demand response	Flexible, price-responsive loads, which may be curtailed or interrupted during system emergencies or when wholesale market prices exceed the utility's supply cost.
demand-side resources	These resources reduce demand. They include energy efficiency, distribution efficiency, generation efficiency, distributed generation and demand response.
DER	Distributed energy resources. Electricity generators like rooftop solar panels that are located below substation level.
DERMS	Distributed Energy Resource Management System
deterministic analysis	Deterministic analysis identifies the least-cost mix of demand-side and supply-side resources that will meet need, given the set of static assumptions defined in the scenario or sensitivity.
DG	distributed generation
distributed energy resources	Small-scale electricity generators like rooftop solar panels, located below substation level.



Term/Acronym	Definition
DLC	direct load control, one of several demand response programs
DMS	distribution management system
DOE	U.S. Department of Energy
DOH	Washington State Department of Health
DR	demand response
DSM	demand-side measure
DSM	demand-side management
DSO	Dispatcher Standing Order
DSP	Delivery System Planning
DSR	demand-side resources
Dth	dekatherms
dual fuel	Refers to peakers that can operate on either natural gas or distillate oil fuel.
EAG	PSE's Equity Advisory Group
EDAM	extended day-ahead market
EE	energy efficiency
EI	Edison Electric Institute
EHD	environmental health disparities
EHEB	Economic, Health and Environmental Benefits Assessment
EIA	U.S. Energy Information Agency
EIA	Washington State Energy Independence Act
EIM	The Energy Imbalance Market operated by CAISO
EIS	environmental impact statement
EITEs	energy-intensive, trade-exposed industries
ELCC	Effective load carrying capacity. The peak capacity contribution of a resource calculated as the change in capacity of a perfect capacity resource that results from adding a different resource with any given energy production characteristics to the system while keeping the 5 percent LOLP resource adequacy metric constant.
EMC	PSE's Energy Management Committee
energy need	The difference between forecasted load and existing resources.
energy storage	A variety of technologies that allow energy to be stored for future use.
EPA	U.S. Environmental Protection Agency
EPRI	Electric Power Research Institute
EPS	Washington state law RCW 80.80.060(4), GHG Emissions Performance Standard



Term/Acronym	Definition
ERU	Emission reduction units. An ERU represents one MtCO ₂ per year.
ESS	energy storage systems
EUE	Expected unserved energy, a reliability metric measured in MWhs that describes the magnitude of electric service curtailment events (how widespread outages may be).
EV	electric vehicle
FERC	Federal Energy Regulatory Commission
FIP	final implementation plan
FLISR	Fault Location, Isolation, Service Restoration
GDP	gross domestic product
GENESYS	The resource adequacy model used by the Northwest Power and Conservation Council (NPCC).
GHG	greenhouse gas
GIS	Geographic Information System
GPM	gas portfolio model
GRC	General Rate Case
GTN	Gas Transmission Northwest
GW	gigawatt
HB 1257	Clean Buildings for Washington Act
HDD	heating degree day
HIC	Highly impacted communities
HILF	high-impact, low-frequency events
HVAC	heating, ventilating and air conditioning
I-937	Initiative 937, Washington state's renewable portfolio standard (RPS), a citizen-based initiative codified as RCW 19.285, the Energy Independence Act.
IAP2	International Association of Public Participation
iDOT	Investment Optimization Tool. An analysis tool that helps to identify a set of projects that will create maximum value.
IGCC	Integrated gasification combined-cycle, generally refers to a model in which syngas from a gasifier fuels a combustion turbine to produce electricity, while the combustion turbine compressor compresses air for use in the production of oxygen for the gasifier.
IJA	Infrastructure Investment and Jobs Act
intermittent resources	Resources that provide power that offers limited discretion in the timing of delivery, such as wind and solar power.
IOU	investor-owned utility
IPP	independent power producer



Term/Acronym	Definition
IRA	Inflation Reduction Act
IRP	integrated resource plan
ISO	independent system operator
ITA	independent technical analysis
ITC	investment tax credit
KORP	Kingsvale-Oliver Reinforcement Project pipeline proposal
kV	kilovolt
kW	kilowatt
kWh	kilowatt hours
LAES	liquid air energy storage
LNG	liquefied natural gas
load	The total of customer demand plus planning margins and operating reserve obligations.
LOLE	Loss of load expectation, a reliability metric that measures the number of days per year with loss of load due to load exceeding available system capacity.
LOLH	Loss of load hours (or loss of load energy), a reliability metric that measures the duration of electric service curtailment events (how long outages may last).
LOLP	Loss of load probability, a reliability metric that measures the likelihood of an electric service curtailment event happening.
LP-Air	vaporized propane air
LSR	Lower Snake River Wind Facility
LTCE	long-term capacity expansion model
LTF	long-term firm transmission
LTF PTP	long-term firm point-to-point transmission
MATS	Mercury Air Toxics Standard
MDEQ	Montana Department of Environmental Quality
MDQ	maximum daily quantity
MDth	One thousand dekatherms or 10,000 therms
MEIC	Montana Environmental Information Center
MESA	Modular Energy Storage Architecture. A protocol for communications between utility control centers and energy storage systems.
Mid-Columbia (Mid-C) market hub	The principle electric power market hub in the Northwest and one of the major trading hubs in the WECC.
MMBtu	million British thermal units
MMtCO ₂ e	million metric tons of CO ₂ equivalent



Term/Acronym	Definition
MSA	metropolitan statistical area
MW	megawatt
MWh	megawatt hour
NAAQS	National Ambient Air Quality Standards, set by the EPA, which enforces the Clean Air Act, for six criteria pollutants: sulfur oxides, nitrogen dioxide, particulate matter, ozone, carbon monoxide and lead.
nameplate capacity	The maximum capacity that a natural gas fired unit can sustain over 60 minutes when not restricted to ambient conditions.
NEPA	National Environmental Policy Act
NERC	North American Electric Reliability Council
net maximum capacity	The capacity a unit can sustain over a specified period of time – in this case 60 minutes – when not restricted by ambient conditions or deratings, less the losses associated with auxiliary loads.
net metering	A program that enables customers who generate their own renewable energy to offset the electricity provided by PSE.
NGV	natural gas vehicles
NO ₂	nitrogen dioxide
NOAA	National Oceanic and Atmospheric Administration
NOS	Network Open Season, a BPA transmission planning process.
NO _x	nitrogen oxides
NPCC	Northwest Power & Conservation Council
NPV	net present value
NRC	Nuclear Regulatory Commission
NREL	National Renewable Energy Laboratories
NRF	Northwest Regional Forecast of Power Loads and Resources, the regional load/balance study produced by PNUCC.
NSPS	New source performance standards, new plants and those with major modifications must meet these EPA standards before receiving permit to begin construction.
NTTG	Northern Tier Transmission Group
NUG	non-utility generator
NWA	non-wires analysis
NWE	NorthWestern Energy
NWGA	Northwest Gas Association
NWP	Northwest Pipeline
NWPP	Northwest Power Pool



Term/Acronym	Definition
OASIS	Open Access Same-Time Information System
OATT	Open Access Transmission Tariff
OMS	outage management system
OTC	once-through cooling
PACE	PacifiCorp East
PACW	PacifiCorp West
PCA	power cost adjustment (electric)
PCORC	power cost only rate case
peak need	Electric or gas sales load at peak energy use times.
peaker (or peaking plants)	Peaker is a term used to describe generators that can ramp up and down quickly in order to meet spikes in need. They are not intended to operate economically for long periods of time like baseload generators.
peaking resources	Quick-starting electric generators that can ramp up and down quickly in order to meet short-term spikes in need, or gas sales resources used to meet load at times when demand is highest.
PEFA	ColumbiaGrid’s planning and expansion functional agreement, which defines obligations under its planning and expansion program.
PEV	plug-in electric vehicle
PG&E	Pacific Gas and Electric Company
PGA	purchased gas adjustment
PGE	Portland General Electric
PHES	pumped hydro energy storage
PHMSA	Pipeline and Hazardous Materials Safety Administration
PIPES Act	Pipeline Inspection, Protection, Enforcement, and Safety Act (2006)
planning margin or PM	These are amounts over and above customer peak demand that ensure the system has enough flexibility to handle balancing needs and unexpected events.
planning standards	The metrics selected as performance targets for a system’s operation.
PLEXOS	An hourly and sub-hourly chronological production simulation model that utilizes mixed-integer programming (MIP) to simulate unit commitment of resources at a day-ahead level, and then simulate the re-dispatch of these resources in real time to match changes in supply and demand on a 5-minute basis.
PM	particulate matter
PNUCC	Pacific Northwest Utilities Coordinating Committee
PNW	Pacific Northwest
POD	point of delivery



Term/Acronym	Definition
portfolio	A specific mix of resources to meet gas sales or electric load.
PPA	Purchased power agreement. A bilateral wholesale or retail power short-term or long-term contract, wherein power is sold at either a fixed or variable price and delivered to an agreed-upon point.
PRP	pipeline replacement program
PSCAA	Puget Sound Clean Air Agency
PSE	Puget Sound Energy
PSEM	Puget Sound Energy Merchant, the part of PSE responsible for obtaining and scheduling the transmission needed to serve PSE loads.
PSIA	Pipeline Safety Improvement Act (2002)
PSRC	Puget Sound Regional Council
PTC	Production Tax Credit, a federal subsidy for production of renewable energy that applied to projects that began construction in 2013 or earlier. When it expired at the end of 2014, it amounted to \$23 per MWh for a wind project's first 10 years of production.
PTP	Point-to-point transmission service, meaning the reservation and transmission of capacity and energy on either a firm or non-firm basis from the point of receipt (POR) to the point of delivery (POD).
PTSA	Precedent Transmission Service Agreement
PUD	public utility district
pumped hydro	Pumped hydro facilities store energy in the form of water, which is pumped to an upper reservoir from a second reservoir at a lower elevation. During periods of high electricity demand, the stored water is released through turbines to generate power in the same manner as a conventional hydropower station.
PV	photovoltaic
R&D	research and development
RA	resource adequacy
RAM	Resource Adequacy Model. RAM analysis produces reliability metrics (EUE, LOLP, LOLH) that allow us to assess physical reliability.
rate base	The amount of investment in plant devoted to the rendering of service upon which a fair rate of return is allowed to be earned. In Washington state, rate base is valued at the original cost less accumulated depreciation and deferred taxes.
RCRA	Resource Conservation Recovery Act
RCW	Revised Code of Washington
RCW 19.285	Washington's state's Energy Independence Act, commonly referred to as the state's renewable portfolio standard (RPS)
RCW 80.80	Washington state law that sets a generation performance standard for electric generating plants that prohibits Washington utilities from building plants or entering into



Term/Acronym	Definition
	long-term electricity purchase contracts from units that emit more than 970 pounds of GHGs per MWh.
REC	Renewable energy credit. RECs are intangible assets, which represent the environmental attributes of a renewable generation project – such as a wind farm – and are issued for each MWh of energy generated from such resources.
REC banking	Washington’s renewable portfolio standard allows for RECs unused in the current year to be “banked” and used in the following year.
redirected transmission	“Redirecting” transmission means moving a primary receipt point on BPA’s system. According to BPA’s business practice, PSE can redirect an existing long-term or short-term, firm or non-firm transmission that it has reserved on BPA’s transmission system. BPA will grant the redirect request as long as there is sufficient capacity on the system to accommodate the change.
regulatory lag	The time that elapses between establishment of the need for funds and the actual collection of those funds in rates.
REM	Residential Energy Management sector, in energy efficiency programs.
repowering	Refurbishing or renovating a plant with updated technology to qualify for Renewable Production Tax Credits under the PATH Act of 2015.
revenue requirement	Rate Base x Rate of Return + Operating Expenses
RFP	request for proposal
RHA	Renewable Hydrogen Alliance
RNG	renewable natural gas
RPS	Renewable portfolio standard. A requirement that electricity retailers acquire a minimum percentage of their power from renewable energy resources. Washington state mandates 3 percent by 2012, 9 percent by 2016 and 15 percent by 2020.
RTO	regional transmission organization
SCADA	Supervisory control and data acquisition that provides real-time visibility and remote control of distribution equipment
SCCT	Simple-cycle combustion turbine, a generating unit capable of ramping up and down quickly to meet peak resource need. Also called a peaker.
scenario	A consistent set of data assumptions that defines a specific picture of the future; takes holistic approach to uncertainty analysis.
SCC	social cost of carbon, also called SCGHG, social cost of greenhouse gases
SCGHG	social cost of greenhouse gases
SCR	selective catalytic reduction
SEIA	Solar Energy Industries Association
SENDOUT	The deterministic gas portfolio model used to help identify the long-term, least-cost combination of integrated supply- and demand-side resources that will meet stated loads.



Term/Acronym	Definition
sensitivity	A set of data assumptions based on the Mid Scenario in which only one input is changed. Used to isolate the effect of a single variable.
SEPA	Washington State Environmental Policy Act
SIP	State Implementation Plan
SNCR	selective non-catalytic reduction
SO2	sulfur dioxide
SOFA system	separated over-fire air system
Solar PV	solar photovoltaic technology
Stochastic analysis	Stochastic risk analysis deliberately varies the static inputs to the deterministic analysis, to test how different portfolios perform with regard to cost and risk across a wide range of potential future power prices, natural gas prices, hydro generation, wind generation, loads, plant forced outages and CO2 prices.
supply-side resources	Resources that generate or supply electric power, or supply natural gas to natural gas sales customers. These resources originate on the utility side of the meter, in contrast to demand-side resources.
T&D	transmission and distribution
TailVar90	A metric for measuring risk defined as the average value of the worst 10 percent of outcomes.
TCPL-Alberta	TransCanada’s Alberta System (also referred to as TC-AB)
TCPL-British Columbia	TransCanada’s British Columbia System (also referred to as TC-BC)
TC-Foothills	TransCanada-Foothills Pipeline
TC-GTN	TransCanada-Gas Transmission Northwest Pipeline
TC-NGTL	TransCanada-Nova Gas Transmission Pipeline
TEPPC	WECC Transmission Expansion Planning Policy Committee
TF-1	Firm gas transportation contracts, available 365 days each year.
TF-2	Gas transportation service for delivery or storage volumes generally intended for use during the winter heating season only.
thermal resources	Electric resources that use carbon-based or alternative fuels to generate power.
TOP	transmission operator
transmission redirect	“Redirecting” transmission means moving a primary receipt point on BPA’s system. According to BPA’s business practice, PSE can redirect an existing long-term or short-term, firm or non-firm transmission that it has reserved on BPA’s transmission system. BPA will grant the redirect request as long as there is sufficient capacity on the system to accommodate the change.
Transport customers	Customers who acquire their own natural gas from third-party suppliers and rely on the natural gas utility for distribution service.



Term/Acronym	Definition
TSR	transmission service request
TSEP	Bonneville Power Administration's transmission service request study and expansion process.
UPC	use per customer
VectorGas	An analysis tool that facilitates the ability to model price and load uncertainty.
VERs	variable energy resources
VPP	virtual power plant
VVO	volt-var optimization
WAC	Washington Administrative Code
WACC	weighted average cost of capital
WCI	Western Climate Initiative
WCPM	Wholesale Purchase Curtailment Model
WECC	Western Electricity Coordinating Council
WEC	Western Energy Company
WEI	Westcoast Energy, Inc.
Westcoast	Westcoast Energy, Inc
Wholesale market purchases	Generally short-term purchases of electric power made on the wholesale market.
WSPP	Western Systems Power Pool
WUTC	Washington Utilities and Transportation Commission
ZLD	zero liquid discharge